

High pressure water blaster from 200bar up to 2.000 bar



Typ CE 20-500 (slime line):

Max. pressure: 500 bar
 Flowrate: 16 l/m
 Pump head: stainl.steel
 Motor cap.: 20 hp – 15 kw
 Protection: IP 54 / F
 Power: 400V-50Hz, 30 A
 440V-60Hz, 28 A
 Frame: stainl.steel
 Dimension: 1100x500x800mm
 Weight: 280 Kg

*Complete with 15m-4 core e-cable,
 20m high pressure water hose
 & 1m stainless steel trigger operated
 lance.*

*Available in ATEX II EX-proof
 Type CEX-20-500*



Typ CE 40-2000 :

Max. pressure: 2.000 bar
 Flowrate: 9 l/m
 Pump head: stainl.steel
 Motor cap.: 40 hp – 30 kw
 Protection: IP 54 / F
 Power: 400V-50Hz, 58 A
 440V-60Hz, 58 A
 Frame: stainl.steel
 Dimension: 1600x1050x1150mm
 Weight: 650 Kg

*Complete with 15m-4 core e-cable, 20m
 high pressure water hose & 1m
 stainless steel trigger operated dump gun.*

*Available in ATEX II EX-proof
 Type CEX-40-2000*



Typ CD 50-2.000 (diesel operated) :

Max. pressure: 2.000 bar
 Flowrate: 9 l/m
 Pump: triplex ceramic plunger
 Motor cap.: 50 hp – 4 cylinder
 Protection: IP 54 / F
 Power: 400V-50Hz, 30 A
 440V-60Hz, 28 A
 Frame: stainl.steel
 Dimension: 1100x500x800mm
 Weight: 280 Kg

*Complete with 20m high pressure water
 hose & 1m stainless steel trigger operated
 dump gun with straight jet and fan jet
 nozzle.*

&

Personal protection equipment for water blaster works



Up to 500 bar:

Boots, gloves, apron, jacket,
 trousers & overall

and helmet with ear
 protector and face shield.



Equipment is stored in heavy
 duty aluminium box with
 contents-list and outside
 marking.



Up to 3.000 bar:

Boots, gloves, apron, jacket,
 trousers & overall

and helmet with ear
 protector and face shield.

All water blaster and protection equipment available within 1 week !